

USAGE AREAS

Sports halls,
swimming pools,
football fields,
basketball fields,
tennis courts

SYSTEM DESCRIPTION

It is a portable system
made from steel
construction.

PROPERTIES

It has a high load capacity
owing to being made from
steel construction. The
advantage of being portable
is it can be turned into
console state providing
free space.

TELESCOPIC TRIBUN

TECHNICAL INFORMATION

Spectator Capacity	It can be chosen between 50 to 500 people.		
Line Number	3 to 6 lines		
Dimensions	Length: 10 to 80m	Width: 1,20 to 4,40m	Height: 1,25 to 2,75m
Seat Model	Spaced - Unspaced		
Framed System	Platforms are manufactured from steel profiles in different dimensions and special molds by combining the gas welding and bolt systems.		
Surface Coatings	Made from pine tree, 12 mm, resistant to water, moisture, dirt, acid, hot and cold weather as well as sun rays, plywood material is used for walkways.		
Carrier System	High strength profiles are used in the production of carrier system. At the same time, every element is supported with two u-profiles connected to each other by ball bearing and rails.		
Wheels	Providing the movement of the telescopic tribune, wheels are polyamid and designed to not to damage the floor. Carrying capacity of the each wheel is 500 kilograms.		
Wheels	Platforms assembled to first platform are moved back and forth using a control button connected to an electric motor .		

APPLICATION METHOD

Infrastructure	Natural ground must be compressed and leveled.
Framed System	It should be produced by using gas welding and bolt systems.
Surface Coatings	After the framed system is installed, surface coatings are made by plywood material.
Carrier System	Legs are assembled by ball bearings and rails.
Electric Motor	Designed for flexible assembly positions, electric motors with maximum thermal capacity are used.

COLORS

Framed System	Standard: Black	Optional: White, Grey, Red, Blue
Stadium Seats	Standard: Red, White, Blue	Optional: Green, Yellow, Orange
Surface Coatings	Standard: Black	



www.stilagrandstand.com

PACKAGE TYPES

Framed System	Manufactured and connected in special dimensions
Stadium Seats	Paletized
Surface Coatings	Paletized

PRODUCT STORAGE CONDITIONS

Electric Motor	It shouldn't be in contact with water.
-----------------------	--

CAPACITY	PRODUCTION TIME	INSTALLATION TIME
50 People	7 Days	2 Days
100 People	14 Days	3 Days
250 People	20 Days	5 Days
500 People	30 Days	7 Days

WARRANTY CONDITIONS

Framed System	5 Years	
Dye	1 - 10 Years	
Electric Motor	5 Years	

TELESCOPIC TRIBUN

EXAMPLE APPLICATIONS

